

## MATERIALS AND STRUCTURES SYMPOSIUM (C2)

## Space Structures II - Development and Verification (Deployable and Dimensionally Stable Structures) (2)

Author: Dr. Jin Li

China Aerospace Science and Technology Corporation (CASC), China

Ms. Cui Hong

China

Mrs. Li Ruizhen

Xi'an Aerospace Composites Materials Institute, China

THERMAL PROPERTY AND MICROSTRUCTURE CONTRAST OF THREE KINDS OF  
CARBON/SILICON CARBIDE COMPOSITES**Abstract**

One of the key technologies for the high performance reconnaissance satellites and large-scale space telescopes with reflectors is fabrication of a very lightweight material with high specific stiffness, low thermal expansion and high thermal conductivity. As the most preferential candidate at present, carbon/silicon carbide (C/SiC) composite has many special advantages, such as: no toxicity, easy assembly, ultra-light weight capability. Several preparation methods can be utilized to make the C/SiC composites green bodies, which are discussed respectively. Thermal property and microstructure contrast of C/SiC via reactive molten infiltration (RMI), chemical vapor reaction (CVR) and RMI-CVR are depicted in this article. It is shown that C/SiC made by RMI possess of lower coefficient of thermal expansion and high thermal conductivity. And after microstructure observation, it was found that C/SiC made by CVR and RMI-CVR have different levels of micro pores. Carbon fibers in the composites mentioned above have been damaged at the same time, while similar state was not found in C/SiC made via RMI. In order to get an isotropy composite and to meet the optical and opto-mechanical requirements, two kinds of carbon fiber preforms, integrated felt and needle-formed fabric felt, were selected and desized firstly to a proper density using chemical vapor infiltration (CVI) to form carbon layers around carbon fibers. Upon completion of the preparation of carbon/carbon C/C composites green bodies, they had been high temperature treated under 1800 and then been light-weight machined to form complicated ribs in the backs and been finished the siliconization process to form the final C/SiC composites. Ultra-light weight capability of the two C/C greenbodies was evaluated. Mechanical, thermal properties of C/SiC composites were evaluated too. It was found that both of two C/C greenbodies can be light-weight machined to form ribs with 1.5mm thickness in each directions, and C/SiC composite with integrated felt preform has a higher isotropy level than the other one.