

66th International Astronautical Congress 2015

MATERIALS AND STRUCTURES SYMPOSIUM (C2)
Advancements in Materials Applications and Rapid Prototyping (9)

Author: Mr. Aniket Marne

College of Engineering, Pune, India, marneas11.meta@coep.ac.in

Ms. Tanvi Katke

College of Engineering, Pune, India, katketm13.mech@coep.ac.in

Ms. Saranga Kamble

College of Engineering, Pune, India, kamblesp12.mech@coep.ac.in

Ms. Bhagyashree Prabhune

India, prabhunebc12.mech@coep.ac.in

Mr. Alimurtaza Kothawala

College of Engineering, Pune, India, kothawalaah12.civil@coep.ac.in

Mr. Abhijit Rathod

College of Engineering, Pune, India, rathodal12.mech@coep.ac.in

Mr. Pradip Bobade

College of Engineering, Pune, India, bobadeps12.mech@coep.ac.in

EMPLOYING RAPID PROTOTYPING TO REDUCE WEIGHT AND OPTIMIZE SELECTED
INTRICATE STRUCTURAL COMPONENTS OF A PICOSATELLITE

Abstract

Rapid prototyping creates a 'prototype' of the CAD model at a fast rate, building the object layer by layer, from the bottom to the top. Swayam is a 1U, low earth orbit pico- satellite and weighs 1 kg. Its payload is passive attitude stabilization, i.e. without consuming on-board power. Swayam will be launched as an auxiliary satellite on board ISRO's polar satellite launch vehicle. In Swayam, non- conducting and non- magnetic materials are needed for protectively housing components like magnet, hysteresis rods and switches from inertial and vibrational loads. Considering various factors such as strength, availability, weight and cost, acrylonitrile butadiene styrene (ABS) has been found to be suitable for these components. Tensile and hardness tests have been performed on ABS for verifying its properties. ABS does not interfere with the satellite's attitude control system. Simulations were run to check the stress levels due vibrations. Stress values so obtained were found to be less than allowable stress values. Components having irregular and intricate shapes such as antenna extension, switch cases were manufactured with ease which is not possible or extremely difficult to manufacture by any other means. These components have been designed considering various stresses to which ABS would be subjected. They have been manufactured using the fused deposition modeling (FDM) type of rapid prototyping technique. The paper explains how RPT was employed to optimize the structure and reduce weight.