

MATERIALS AND STRUCTURES SYMPOSIUM (C2)
Advancements in Materials Applications and Rapid Prototyping (9)

Author: Dr. yinyin zhang
McGill Univeristy, Canada, yinyin.zhang@mail.mcgill.ca

DRY SLIDING WEAR BEHAVIOUR OF SELF-LUBRICATING COPPER MOLYBDENUM
DISULFIDE COMPOSITES

Abstract

Molybdenum disulfide (MoS₂) is the most frequently used solid lubricant in space tribology because it produces the lowest friction coefficients ever measured in vacuum, as well as a long lifetime and low wear rate. The traditional method of providing solid lubrication is to deposit a thin film of MoS₂ on a metal surface of a machine component. However, this approach exhibits an inherent disadvantage that the surface film only has a finite lifetime. The most attractive alternative is to fabricate a bulk metallic material that is reinforced with solid lubricant. Such form of “built-in” solid lubrication provides replenishment of solid lubricant as wear continuous, leading to an improved lifetime of the components. In the present work, a copper molybdenum disulfide composite was fabricated by cold spray and its tribological performance was investigated by in situ tribometry, which permits observation of real-time friction and wear processes occurring at “buried” sliding interfaces. Third body physical and chemical processes, such as forming, loss, replenishment of MoS₂ transferfilm and tribofilms, as well as sliding-induced chemical change were observed for sapphire sliding against Cu-MoS₂ composites. It was demonstrated that a small amount of solid lubricant (1.8–0.99 wt.

This work provides an understanding into friction and wear mechanisms of MoS₂ reinforced metal matrix composites subjected to dry sliding testing. It exhibits lower friction and much longer endurance, therefore has a potential to be used for space tribological applications.