

EARTH OBSERVATION SYMPOSIUM (B1)
Future Earth Observation Systems (2)

Author: Mr. Kenneth Sinclair
York University, Canada, ksinc@yorku.ca

NANOSATELLITE MISSION OVERVIEW WITH A SLAB WAVEGUIDE SPATIAL HETERODYNE
SPECTROMETER PAYLOAD**Abstract**

The mission architecture and concept of a new type of waveguide device, a multiaperture Fourier-transform planar waveguide spectrometer[1], is presented. These spectrometers offer high resolution, increased throughput (etendue), no moving parts and are compatible with a nanosatellite platform[2]. Development of miniature infrared spectrometers that are robust and environmentally reliable is of great interest for space-borne sensing and spectral imaging.

The spectrometer will use a solar occultation configuration to detect the 1.36 μ m waveband allowing concentrations of water vapor in Earth's atmosphere to be measured[3]. The objective of the spectrometer is to make global measurements of water vapor from 10 to 80km above Earth's surface at 1km vertical resolution.

Non-uniformities of input brightness and fabrication errors will affect the performance of the waveguides, therefore focus will be given to calibration algorithms and data processing algorithms developed to mitigate this. The output from the array detector comes in the form of a power interferogram which is Fourier Transformed in order to perform spectral retrieval. The most challenging aspects of the mission's concept including the occultation configuration and instrument's coverage are presented.

REFERENCES

1. M. Florjańczyk, P. Cheben, S. Janz, A. Scott, B. Solheim, and D.-X. Xu, "Multiaperture planar waveguide spectrometer formed by arrayed Mach-Zehnder interferometers," *opt. expr.* 15(26), 18176-18189 (2007).
2. M. Florjańczyk, P. Cheben, S. Janz, B. Lamontagne, J. Lapointe, A. Scott, B. Solheim, and D.-X. Xu, "Slab waveguide spatial heterodyne spectrometers for remote sensing from space," *Optical sensors 2009. Proceedings of the SPIE, Volume 7356 (2009).*, pp. 73560V-73560V-7 (2009).
3. A. Scott, M. Florjańczyk, P. Cheben, S. Janz, B. Solheim, and D.-X. Xu, "Micro-interferometer with high throughput for remote sensing." *MOEMS and Miniaturized Systems VIII. Proceedings of the SPIE, Volume 7208 (2009).*, pp. 72080G-72080G-7 (2009).