

41st STUDENT CONFERENCE (E2)
Student Conference – Part 1 (1)

Author: Mr. Nishchay Mhatre
College of Engineering Pune, India, mhatrens07.it@coep.ac.in

Mr. Shravan Aras
College of Engineering Pune, India, arassg08.comp@coep.ac.in

A HYBRID APPROACH TO RADIATION FAULT TOLERANCE IN SMALL SATELLITE
APPLICATIONS**Abstract**

Radiation presents a significant hazard, in the form of Single Event Upsets (SEU), to small satellite missions in Low Earth Orbit, due to the proximity of the orbits to the Van Allen radiation belts. Radiation-hardened electronics are prohibitively expensive and hard to source for small satellite projects, particularly student satellites. However, using a mixture of fault tolerant circuitry and error correction coding, we can overcome the SEU hazards for an insignificant cost. Such a hybrid radiation fault tolerance method for a pico-satellite On Board Computer (OBC), is described in this paper. These radiation fault tolerance features have been designed as part of the COEP Communication Satellite, a student designed Ham communication pico-satellite. This work also covers the integration of these features with the overall design of the OBC. The aim of this design is to ensure protection and recovery from SEU's in the proposed orbit for the duration of the mission, without depending on expensive radiation-hardened devices. A combination of 'watch-dog' hardware, that extracts the OBC from possible hang-ups and error correction coding (ECC) in program memories has been used. An innovative method for achieving Triple Modular Redundancy (TMR) in program memory, without special hardware support, has been developed. A Hamming Code has been used to correct all single bit errors in memories. A constant-time Single Error Correction algorithm for fast 'Data-Scrubbing' has been developed and implemented using the ARM based micro-controller of the OBC. Tests on the hardware and software have proved their ability to correct hang-ups and errors. Correction of single bit flips in the OBC memories has demonstrated in constant time, thus assuring real-time operation. OBC hang-ups have been successfully resolved by the watch-dog in real time. A 50 percent saving in storage space over conventional TMR has been achieved. Finally, the fault tolerance features have been successfully integrated into the satellite OBC.