

SPACE DEBRIS SYMPOSIUM (A6)  
Hypervelocity Impacts and Protection (3)

Author: Dr. Joshua Miller  
National Aeronautics and Space Administration (NASA), Johnson Space Center, United States,  
joshua.e.miller@nasa.gov

Dr. Eric Christiansen  
National Aeronautics and Space Administration (NASA), Johnson Space Center, United States,  
Eric.L.Christiansen@nasa.gov

Mr. Bruce Davis  
National Aeronautics and Space Administration (NASA), Johnson Space Center, United States,  
bruce.a.davis1@nasa.gov

## MULTI-SHOCK SHIELD PERFORMANCE AT 15 MJ FOR CATALOGUED DEBRIS

**Abstract**

While orbital debris of ten centimeters or more are tracked and catalogued, the difficulty of finding and accurately accounting for forces acting on the objects near the ten centimeter threshold results in both uncertainty of their presence and location. These challenges result in difficult decisions for operators balancing potential costly operational approaches with system loss risk. In this paper, numerical simulations and an experiment using the multi-shock shield system is described for a cylindrical projectile composed of Nylon, aluminum and void that is approximately 8 cm in diameter and 10 cm in length weighing 0.6 kg. The projectile impact represents a 15 MJ deposition of kinetic energy into the multi-shock shield normal to the surface. The multi-shock shield system has been optimized to facilitate the fragmentation, spread and deceleration of the projectile remnants using hydrodynamic simulations of the impact event. The characteristics and function of each of the layers of the multi-shock system will be discussed along with considerations for deployment and improvement.