

MATERIALS AND STRUCTURES SYMPOSIUM (C2)  
Smart Materials and Adaptive Structures (5)

Author: Mr. Joel Quintana  
University of Texas at El Paso, United States, jquintana@utep.edu

Dr. Jack Chessa  
University of Texas at El Paso, United States, jfchessa@utep.edu  
Dr. Virgilio Gonzalez  
University of Texas at El Paso, United States, vgonzalez3@utep.edu

LOCATION OF A MAXIMUM DEFLECTION POINT WITH FIBER BRAGG GRATINGS IN  
POLARIZATION-MAINTAINING OPTICAL FIBER**Abstract**

With the recent prevalence of composite laminated or fully composite, reusable rocket structures, it is of critical need to evaluate the structural health of each rocket before, after and possibility during each launch. FBG sensors have proven to be excellent devices for structural health monitoring (SHM) and are quickly becoming economically advantageous over electronic, conventional strain gauges. FBG strain sensors offer many well-known advantages and are exceptionally accurate when measuring strains that are orientated in the longitudinal direction with respect to the sensor. FBG sensors written in PM fiber offer additional dimensions of strain measurement per sensing element, reducing the number of sensing units per area.

We build a strain profile of a flat composite plate with concentrated load acting at the center. The FBG PM sensors are placed at random on the surface of the plate. We then calculate spectral shifts caused by the applied axial and traversal strains on the sensors and compare to a predetermined optical baseline. From the optical signal, the shift deltas in wavelength are parsed to correspond to axial and transversal strains. This exercise validates a method of optical detection and shift calculation for multi-axis sensors as an automated, integrated system.

Of particular interest is defining the minimum number of sensors required to detect a critical flaw. In this spirit, this paper defines the theoretical minimum number of the PM FBG sensing elements needed to detect a point of maximum deflection on the panel. The point of maximum deflection has been located on a Cartesian plane by formulating orthogonal vectors from the strain tensor of each sensing element at the its location. A group of vector intersects with the minimum Euclidian distance from each other correspond to said point.

- 1 Udd, et al. "Multidimensional strain field measurements using fiber optic grating sensors," Proc. SPIE 3986, p.254 (2000).
- 2 Bosia, et al. "Characterization of the response of fibre Bragg grating sensors subjected to a two-dimensional strain field," Smart materials and Structures 12(6), 925 (2003).
- 3 Botero-Cadavid, et al. "Spectral Properties of Locally Pressed Fiber Bragg Gratings Written in Polarization Maintaining Fibers," Journal of Lightwave Technology 28(9), 1291-1297 (2010).
- 4 Lawrence, Craig Michael. "Embedded fiber-optic strain sensors for process monitoring of composites." (1997).
- 5 Timoshenko, Stephen P., and Sergius Woinowsky-Krieger. Theory of plates and shells. McGraw-hill, 1959.