

IAF MATERIALS AND STRUCTURES SYMPOSIUM (C2)

Space Structures II - Development and Verification (Deployable and Dimensionally Stable Structures) (2)

Author: Mr. Cristovao Cardoso

Hps-high Performance Structures, Lda, Portugal, cardoso@hps-lda.pt

Mr. Pedro Teixeira

Hps-high Performance Structures, Lda, Portugal, teixeira@hps-lda.pt

Mr. Joao Pedro Loureiro

Hps-high Performance Structures, Lda, Portugal, loureiro@hps-lda.pt

Mr. Ivo Costa

Hps-high Performance Structures, Lda, Portugal, costa@hps-lda.pt

Mr. Luis Moreira

INEGI, Portugal, lcmoreira@inegi.up.pt

Mr. Jhonny Rodrigues

INEGI, Portugal, jsrodrigues@inegi.up.pt

Mr. Clifford Ashcroft

The Netherlands, Clifford.Ashcroft@esa.int

Mr. Ludovic Puig

ESA, The Netherlands, Ludovic.Puig@esa.int

TEST AND ANALYTIC MODEL RESULTS CORRELATION FOR DEPLOYABLE TRUSSWORK MAST

Abstract

Under the ESA activity for Large Stable Deployable Structures for Future Science Missions (LADS), HPS is developing a deployable mast for X-Ray telescope, 12m long, 4m wide, to hold the 1ton instrument, to reach TRL 5 (deployment mechanism not included).

An analytic model was developed to calculate the mast: deployment error, friction error, thermal expansion deformation, moisture absorption deformation, bending stiffness, shear stiffness, torsion stiffness, limit loads, mass, etc.

Material and elementary tests are now being finalized. The results from these tests will be used as inputs in the analytic model.

A 2m long breadboard, composed of 2 bays was built and will be tested during March and April. These tests will measure: deployment error, friction error, bending + shear stiffness, torsion stiffness, mast mass and mast damping.

This paper will present and correlate the predictions made with the analytic model and the measurements made on the 2 bays breadboard.