

25th IAA SYMPOSIUM ON SMALL SATELLITE MISSIONS (B4)  
Generic Technologies for Small/Micro Platforms (6A)

Author: Mr. Carl Treudler  
German Aerospace Center (DLR), Germany

Dr. Heike Benninghoff  
German Aerospace Center (DLR), Germany

Mr. Kai Borchers  
German Aerospace Center (DLR), Germany

Mr. Kilian Höflinger  
Simulation and Software Technology, Deutsches Zentrum für Luft- und Raumfahrt e.V. (DLR), Germany

Mr. Bernhard Brunner  
German Aerospace Center (DLR), Germany

Mr. Jan Cremer  
German Aerospace Center (DLR), Germany

Mr. Michael Dumke  
German Aerospace Center (DLR), Germany

Mr. Thomas Gärtner  
German Aerospace Center (DLR), Germany

Mr. Jörg Langwald  
German Aerospace Center (DLR), Germany

Mr. Daniel Lüdtke  
German Aerospace Center (DLR), Germany

Ms. Ting Peng  
German Aerospace Center (DLR), Germany

Mr. Eicke-Alexander Risse  
German Aerospace Center (DLR), Germany

Dr. Kurt Schwenk  
German Aerospace Center (DLR), Germany

Mr. Martin Stelzer  
German Aerospace Center (DLR), Germany

Mr. Moritz Ulmer  
German Aerospace Center (DLR), Germany

Mr. Simon Vellas  
German Aerospace Center (DLR), Germany

Mr. Karsten Westerdorff  
German Aerospace Center (DLR), Germany

SCOSA - SCALABLE ON-BOARD COMPUTING FOR SPACE AVIONICS

**Abstract**

Computational demands on spacecraft have continuously increased for years whereby available space qualified hardware is not capable of satisfying these requirements completely. This paper introduces a way

to overcome this problem by combining highly reliable space qualified hardware with highly performant commercial off-the-shelf (COTS) components. This combination of hardware enabled us to develop a new type of on-board computing (OBC) system, called ScOSA (Scalable On-Board Computing for Space Avionics).

A ScOSA system uses a distributed approach whereas it consists of multiple nodes. They are classified as reliable or high performance nodes. The reliable nodes are based on radiation-hardened Leon3 processors, the high-performance nodes on COTS Xilinx Zynq (CPU and FPGA). All nodes are connected by a SpaceWire network with a meshed topology that provides redundant data paths to establish fault tolerance. A large number of existing systems can be connected to our system given that SpaceWire is widely used within the space domain.

ScOSA has additional capabilities during operation that set it apart from traditional on-board computing systems. During runtime a dynamic reconfiguration of the whole system can be performed. By this, faulty nodes can be removed or recovered nodes can be reintegrated into the system. Additionally, computation tasks can be started, stopped or shifted between all active nodes. Also, connected FPGAs can be reprogrammed. As a consequence, these reconfiguration capabilities can be used to fulfill changing requirements without exchanging the underlying hardware. This can also be used to handle different spacecraft modes or mission phases.

The contribution of this paper is to explain the details of the ScOSA architecture, implementation and its functionality. Additionally, we will show the results of running representative applications from the space robotics, earth-observation and satellite avionics domains. These applications were selected for evaluating the system capabilities and include, among others, autonomous navigation and capture operations, stereo image processing and optical ship detection. Testing and demonstration will be done in Hardware-in-the-Loop simulators or on robotic testbeds (namely DLR's EPOS and OOS-Sim).