

46th STUDENT CONFERENCE (E2)
Student Conference - Part 2 (2)

Author: Mr. Ken Mitchell

American Institute of Aeronautics and Astronautics (AIAA), United States, kmtchl15@memphis.edu

THERMAL CONDUCTIVITY AND SPECIFIC HEAT MEASUREMENTS OF AN
RTV-655/POLYIMIDE AEROGEL COMPOUND AT 77K AND 298K**Abstract**

The ability to store cryogenic liquids for long duration space missions is essential to future manned space exploration. Boil-off of cryogenics due to incident solar radiation over time leads to pressurization of a cryogenic tank. An ideal tank construction material would have low thermal conductivity and would retain its structural integrity through extreme temperatures. In previous research, a small-scale RTV-655/polyimide aerogel cryogenic liquid storage tank was constructed and tested to assess the performance of the compound material. Further development of RTV-655/polyimide aerogel cryogenic tanks is contingent on performing computational studies to optimize the design and minimize costly experiments. Thermal conductivity and specific heat values of the combination of RTV-655 and polyimide aerogel have not been published at cryogenic temperatures. The Hot Disk Thermal Constants Analyzer in accordance with ISO standard 22007-2:2015 is utilized to measure thermal conductivity, specific heat, and thermal diffusivity values for RTV-655 and polyimide aerogel at cryogenic temperatures.