

17th IAA SYMPOSIUM ON SPACE DEBRIS (A6)  
Operations in Space Debris Environment, Situational Awareness (7)

Author: Dr. Elena Vellutini  
Italian Space Agency (ASI), Italy

Dr. Germano Bianchi  
INAF - IRA, Italy  
Dr. Carmen Pardini  
ISTI-CNR, Italy  
Dr. Luciano Anselmo  
ISTI-CNR, Italy  
Dr. Pierluigi Di Lizia  
Politecnico di Milano, Italy  
Dr. Mauro Massari  
Politecnico di Milano, Italy  
Mr. Matteo Losacco  
Politecnico di Milano, Italy  
Dr. Fabrizio Piergentili  
Sapienza University of Rome, Italy  
Mr. Marco Acernese  
Sapienza University of Rome, Italy  
Mr. Lorenzo Mariani  
Sapienza University of Rome, Italy  
Mr. Shariar Hadji Hossein  
Sapienza University of Rome, Italy  
Dr. Tonino Pisanu  
National Institute for Astrophysics, Italy  
Dr. Enrico Urru  
INAF - Istituto Nazionale di AstroFisica, Italy  
Dr. Luca Schirru  
National Institute for Astrophysics (INAF), Italy  
Mr. Fabio Monaci  
Italian Air Force , Italy  
Mr. Moreno Peroni  
Italian Air Force , Italy  
Mr. Andrea Cecchini  
Italian Ministry of Defense, Italy  
Mr. Giuseppe D'Amore  
Agenzia Spaziale Italiana (ASI), Italy  
Dr. Ettore Perozzi  
Agenzia Spaziale Italiana (ASI), Italy  
Dr. Luca Lama  
INAF - IRA, Italy  
Mr. Claudio Bortolotti

INAF - IRA, Italy  
Mr. Mauro Roma  
INAF - IRA, Italy  
Mr. Andrea Maccaferri  
INAF, Italy  
Prof. Fabio Santoni  
Sapienza University of Rome, Italy  
Dr. Leonardo Parisi  
Sapienza University of Rome, Italy  
Mr. Giovanni Purpura  
Politecnico di Milano, Italy

## DATA FUSION APPLICATION FOR IMPROVING ORBIT DETERMINATION AND RE-ENTRY PREDICTIONS

### Abstract

Re-entries of space objects are common occurrences, which take place every day; however, the risks related to these events are marginal for both people and ground infrastructures. Nevertheless, the re-entry prediction of uncontrolled objects is a key capability in order to opportunely monitor the decaying of large intact spacecraft and upper stages which, in particular cases, could pose a risk for people on the ground, such as the uncontrolled re-entry of the Chinese space station Tiangong-1 in 2018. Surveying and providing early warning of uncontrolled re-entries of large space debris is one of the main objectives of the EUSST support framework adopted by the European Commission in 2014. This initiative is implemented by a Consortium initially formed by five European Member States (France, Germany, Italy, Spain, United Kingdom), and expanded from 2019 with three additional EU Member States (Poland, Portugal, Romania). The EUSST service provision is facilitated by the EUSatCen and the three SST services, Re-entry, Collision Avoidance and Fragmentation, are provided by different member states. Italy is currently in charge of Re-entry and Fragmentation services, and the current national architecture of the system is expected to evolve to improve their provision. In this perspective, an added value for the system can be given by the implementation of data fusion between radar and passive optical sensors. This technique could supply additional information about the object's dynamics (i.e. attitude motion, tumbling rate and tumbling axis orientation), which is a critical point for the uncontrolled re-entry of massive objects; moreover, it may be helpful for more refined predictions during the final phases of the decay. In addition to that, a network of sensors specifically dedicated to re-entry has the benefit of supporting the orbit determination and propagation accuracy for the whole EUSST Consortium service provision. The enhanced tracking capabilities achievable through the integration of radar and optical data have been investigated with an observation campaign conducted by tracking different re-entering objects. The acquired measures have been analysed by employing innovative data fusion techniques, and exploited to improve the orbital estimates of the objects. The solutions reliability has been verified through additional independent data and subsequent measurements. For each case, a comparison between the proposed approach and analogous scenarios not involving data fusion has been performed. The results, that will be exposed in detail, show the data fusion technique to provide a dramatic improvement in terms of orbit determination and re-entry prediction accuracy.