

IAF SPACE SYSTEMS SYMPOSIUM (D1)
Space Systems Architectures (2)

Author: Dr. Murray Kerr
Deimos Space S.L., Spain, murray.kerr@deimos-space.com

Dr. Stefania Tonetti
Deimos Space SLU, Spain, stefania.tonetti@deimos-space.com
Ms. Stefania Cornara
Deimos Space S.L., Spain, stefania.cornara@deimos-space.com
Dr. Aniello Fiengo
Deimos Space SLU, Spain, aniello.fiengo@deimos-space.com
Mr. Juan Ignacio Bravo
Deimos Space SLU, Spain, juan-ignacio.bravo@deimos-space.com
Dr. Robert Hinz
Deimos Space SLU, Spain, robert.hinz@deimos-space.com
Mr. Antonio Latorre
Deimos Space SLU, Spain, antonio.latorre@deimos-space.com
Mr. Francisco Membibre
Deimos Space SLU, Spain, francisco.membibre@deimos-space.com
Dr. Chiara Solimini
Deimos Space SLU, Spain, chiara.solimini@deimos-space.com
Dr. Stefan Wiehle
German Aerospace Center (DLR), Germany, stefan.wiehle@dlr.de
Mr. Helko Breit
DLR (German Aerospace Center), Germany, helko.breit@dlr.de
Mr. Björn Tings
German Aerospace Center (DLR), Germany, bjoern.tings@dlr.de
Prof. Otto Koudelka
Graz University of Technology (TU Graz), Austria, koudelka@tugraz.at
Dr. Franz Teschl
Graz University of Technology (TU Graz), Austria, franz.teschl@tugraz.at
Prof. Enrico Magli
Politecnico di Torino, Italy, enrico.magli@polito.it
Dr. Tiziano Bianchi
Politecnico di Torino, Italy, tiziano.bianchi@polito.it
Mr. Andrea Migliorati
Politecnico di Torino, Italy, andrea.migliorati@polito.it
Mr. Paolo Motto Ros
Politecnico di Torino, Italy, paolo.mottoros@polito.it
Mr. Michele Caon
Politecnico di Torino, Italy, michele.caon@polito.it
Mr. Riccardo Freddi
OHB Italia SpA, Italy, rfreddi@cgspace.it
Mr. Michele Benetti

OHB Italia SpA, Italy, mbenetti@cgspace.it
Mr. Fabio Milani
OHB Italia SpA, Italy, fmilani.ext@cgspace.it
Mr. Guido Curci
OHB Italia SpA, Italy, gcurci.ext@cgspace.it
Ms. Silvia Fraile
Deimos Imaging, Spain, silvia.fraile@deimos-imaging.com
Ms. Lucia Garcia
Deimos Imaging, Spain, lucia.garcia@deimos-imaging.com
Ms. Cecilia Marcos
Agencia Estatal de Meteorología, Spain, cmarcosm@aemet.es

EO-ALERT: A NOVEL ARCHITECTURE FOR THE NEXT GENERATION OF EARTH OBSERVATION SATELLITES SUPPORTING RAPID CIVIL ALERTS

Abstract

Satellite Earth Observation (EO) data is ubiquitously used in many applications, providing basic services to society, such as environment monitoring, emergency management and civilian security. Due to the increasing request of EO products by the market, the classical EO data chain generates a severe bottleneck problem, further exacerbated in constellations. A huge amount of EO raw data generated on-board the satellite must be transferred to ground, slowing down the EO product availability, increasing latency, and hampering the growth of applications in accordance with the increased user demand. This paper provides an overview of the results achieved by the EO-ALERT project (<http://eo-alert-h2020.eu/>), an H2020 European Union research activity. EO-ALERT proposes the definition and development of the next-generation EO data processing chain, based on a novel flight segment architecture that moves optimised key EO data processing elements from the ground segment to on-board the satellite, with the aim of delivering the EO products to the end user with very low latency (quasi-real-time). EO-ALERT achieves, globally, latencies below five minutes for EO products delivery, achieving latencies below 1 minute in some scenarios. The proposed architecture solves the above challenges through a combination of innovations in the on-board elements of the data chain and the communications. Namely, the architecture introduces innovative technological solutions, including on-board reconfigurable data handling, on-board image generation and processing for the generation of alerts (EO products) using Artificial Intelligence (AI), on-board data compression and encryption using AI, high-speed on-board avionics, and reconfigurable high data rate communication links to ground, including a separate chain for alerts with minimum latency and global coverage. The paper presents the proposed architecture, its performance and hardware, considering two different user scenarios; ship detection and extreme weather observation/nowcasting. The results show that, when implemented using COTS components and available communication links, the proposed architecture can deliver alerts to ground with latency lower than five minutes, for both SAR and Optical missions, demonstrating the viability of the EO-ALERT concept and architecture. The paper also discusses the implementation on an avionics test bench for testing the architecture with real EO data, with the aim of demonstrating that it can meet the requirements of the considered scenarios in terms of detection performance and provides technologies at a high TRL (4-5). When proven, this will open unprecedented opportunities for the exploitation of civil EO products, especially in latency sensitive scenarios, such as disaster management.