IAF MATERIALS AND STRUCTURES SYMPOSIUM (C2)

Space Environmental Effects and Spacecraft Protection (6)

Author: Dr. Peter C.E. Roberts

The University of Manchester, United Kingdom, peter.c.e.roberts@manchester.ac.uk

Dr. Nicholas H. Crisp

The University of Manchester, United Kingdom, nicholas.crisp@manchester.ac.uk

Dr. Steve Edmondson

The University of Manchester, United Kingdom, stephen.edmondson@manchester.ac.uk Dr. Sarah Haigh

The University of Manchester, United Kingdom, sarah.haigh@manchester.ac.uk Mr. Brandon A. Holmes

The University of Manchester, United Kingdom, brandon.holmes@postgrad.manchester.ac.uk Ms. Sabrina Livadiotti

The University of Manchester, United Kingdom, sabrina.livadiotti@postgrad.manchester.ac.uk Mr. Alejandro Macario Rojas

The University of Manchester, United Kingdom, alejandro.macariorojas@manchester.ac.uk Dr. Vitor Oiko

The University of Manchester, United Kingdom, vitor.oiko@manchester.ac.uk Dr. Katharine Smith

University of Manchester, United Kingdom, kate.smith@manchester.ac.uk Ms. Luciana Sinpetru

The University of Manchester, United Kingdom, luciana.sinpetru@manchester.ac.uk Dr. Jonathan Becedas

Elecnor Deimos Satellite Systems, Spain, jonathan.becedas@elecnor-deimos.es Ms. Rosa María Domínguez

Elecnor Deimos Satellite Systems, Spain, rosa-maria.dominguez@elecnor-deimos.es Ms. Valeria Sulliotti-Linner

Elecnor Deimos Satellite Systems, Spain, valeria.sulliotti@deimos-space.com Mr. Simon Christensen

GomSpace Aps, Denmark, sic@gomspace.com

Mr. Thomas Kauffman Jensen

GomSpace Aps, Denmark, thkj@gomspace.com

Mr. Jens Nielsen

GomSpace Aps, Denmark, jni@gomspace.com

Dr. Morten Bisgaard

GomSpace ApS, Denmark, bisgaard@gomspace.com

Mr. Yung-An Chan

Institute of Space Systems, University of Stuttgart, Germany, chan@irs.uni-stuttgart.de

Dr. Georg H. Herdrich

University of Stuttgart, Germany, herdrich@irs.uni-stuttgart.de

Mr. Francesco Romano

Institute of Space Systems, University of Stuttgart, Germany, romano@irs.uni-stuttgart.de Prof. Stefanos Fasoulas

University of Stuttgart, Germany, fasoulas@irs.uni-stuttgart.de

Mr. Constantin Traub

Institute of Space Systems, University of Stuttgart, Germany, ctraub@irs.uni-stuttgart.de

Dr. Daniel Garcia-Almiñana

UPC-BarcelonaTECH, Spain, daniel.garcia@upc.edu

Ms. Marina García-Berenguer

UPC-BarcelonaTECH, Spain, marina.garcia.berenguer@upc.edu

Dr. Silvia Rodriguez-Donaire

UPC-BarcelonaTECH, Spain, silvia.rodriguez-donaire@upc.edu

Dr. Miquel Sureda

UPC-BarcelonaTECH, Spain, miquel.sureda@upc.edu

Dr. Dhiren Kataria

University College London (UCL), United Kingdom, d.kataria@ucl.ac.uk

Ms. Badia Belkouchi

Euroconsult, France, belkouchi@euroconsult-ec.com

Mr. Alexis Conte

Euroconsult, France, a.conte@euroconsult-ec.com

Mr. Simon Seminari

Euroconsult, France, s.seminari@euroconsult-ec.com

Mrs. Rachel Villain

Euroconsult, France, villain@euroconsult-ec.com

Ms. Ameli Schwalber

concentris research management gmbh, Germany, ameli.schwalber@concentris.de

DISCOVERER - DEVELOPING TECHNOLOGIES TO ENABLE COMMERCIAL SATELLITE OPERATIONS IN VERY LOW EARTH ORBITS

Abstract

The DISCOVERER project is developing technologies to enable the sustained-operation of satellites in very low Earth orbits (VLEO) for communications and remote sensing applications. Operating closer to the surface of the Earth significantly reduces latency for communications applications and improves link budgets, whilst remote sensing also benefits from improved link budgets, the ability to have higher resolution or smaller instruments, all of which provide cost benefits. In addition, all applications benefit from increased launch mass to lower altitudes, whilst end-of-life removal is ensured due to the increased atmospheric drag. However, this drag must also be minimised and compensated for.

DISCOVERER is developing several critical technologies to enable commercially viable operations in at these lower altitudes:

- materials that encourage specular reflections of the residual atmosphere in free molecular flows, which can be used in concert with the design of external satellite geometries to minimise drag, and generate lift for aerodynamic attitude and orbit control
- aerodynamic attitude and orbit control methods, which are essential at lower altitudes to complement traditional attitude control actuators.
- atmosphere breathing electric propulsion (ABEP), combining an optimised atmospheric intake with a inductive plasma thruster (IPT), to effectively remove the lifetime limits resulting from finite propellant for drag compensation.
- environment monitoring payloads with the potential to provide active feedback for aerodynamic attitude and orbit control.

2020 is an exciting year for DISCOVERER. Highlights include:

• the commissioning of our Rarefied Orbital Aerodynamics Research facility (ROAR) which can characterise the reemission characteristics of a beam of atomic oxygen (the predominant gas species in VLEO) at orbital velocities with material samples, and thereby determine their reflection properties.

- the first ignition of our ABEP prototype IPT and test of sub-scaled intakes in ROAR.
- the launch of our Satellite for Orbital Aerodynamics Research (SOAR) which will validate the aerodynamic performance of materials and demonstrate aerodynamic manoeuvres.
- the return of materials samples from the MISSE exposure facility on the International Space Station demonstrating the survivability of candidate novel materials.

This paper will provide highlights from the developments, and demonstrate the potential for a new class of aerodynamic commercial satellites operating at altitudes below the International Space Station.

The DISCOVERER project has received funding from the European Union's Horizon 2020 research and innovation programme under grant agreement No 737183.