## 18th IAA SYMPOSIUM ON BUILDING BLOCKS FOR FUTURE SPACE EXPLORATION AND DEVELOPMENT (D3)

Space Technology and System Management Practices and Tools (3)

Author: Prof. Xiu-Tian Yan University of Strathclyde, United Kingdom

Dr. Nassir W. Oumer DLR (German Aerospace Center), Germany Mr. Pierre Letier Space Applications Services (SAS), Belgium

## VISION ENABLED SMART MANIPULATIONS FOR IN-SPACE CONSTRUCTION

## Abstract

In recent years, vision systems and in particular the algorithms developed to process images have made significant advancement in recognizing various types of objects in facial recognition, agricultural objects recognition, engineering parts and so forth. Vision hardware systems become much more accessible. Vision systems therefore have the potential to allow automatic monitoring and manoeuvring of spacecrafts and robots in space. Meaningful and critical spatial and geometric information of a targeted object can be extracted from camera images, and can be communicated to a robotic planner to enable real time replanning based on new information identified. This could also be communicated to a human operator for immediate reaction to unforeseen events. Such vision systems have been deployed successfully in factories and terrestrial robotic applications, but they face unique challenges in space where the environment is unstructured and could also be unknown. Unreliable and unstable illumination affect the image quality over extended observations. Furthermore, satellites and spacecrafts are composed of highly reflective material and parts might no longer be recognizable due to excessive reflected brightness. As the space industry practice requires the deployment of high reliable systems, it is imperative that these problems are systematically analysed and addressed before a vision system can become operative in space. This article is a step forward toward reliable space vision systems. It introduces a systematic approach to measuring and validating the performance of vision algorithms under different illumination conditions. Firstly, a test environment, a test rig purposely built for space applications and a new image dataset for testing 3D surface reconstruction algorithms are presented. Thereafter, the performance measures and test results from object localization algorithms are described, supporting a wider European space demonstrator project MOSAR which aims to demonstrate the capabilities of autonomous assemblies of spacegrafts using a walking manipulator.