

IAF SPACE EXPLORATION SYMPOSIUM (A3)  
Moon Exploration – Part 1 (2A)

Author: Dr. Francesco Topputo  
Politecnico di Milano, Italy

Mr. Gianmario Merisio  
Politecnico di Milano, Italy

Mr. Carmine Giordano  
Politecnico di Milano, Italy

Mr. Vittorio Franzese  
Politecnico di Milano, Italy

Dr. Mauro Massari  
Politecnico di Milano, Italy

Dr. Pierluigi Di Lizia  
Politecnico di Milano, Italy

Mr. Demetrio Labate  
Leonardo Spa, Italy

Mr. Giuseppe Pilato  
Manpower c/o Leonardo, Italy

Dr. Emanuele Costa  
Leonardo Spa, Italy  
Dr. Angelo Cervone

Delft University of Technology (TU Delft), The Netherlands  
Dr. Stefano Speretta

Delft University of Technology (TU Delft), The Netherlands  
Dr. Alessandra Menicucci

Delft University of Technology (TU Delft), The Netherlands  
Mr. Eric Bertels

ISIS - Innovative Solutions In Space B.V., The Netherlands  
Mr. A Thorvaldsen  
Norway

Mr. A Kukharenka  
Norway

Mr. Johan Vennekens

ESA - European Space Agency, The Netherlands  
Dr. Roger Walker

European Space Agency (ESA), The Netherlands

CURRENT STATUS OF LUMIO MISSION: CHARACTERIZING LUNAR METEOROID IMPACTS  
WITH A CUBESAT

**Abstract**

The Lunar Meteoroid Impact Observer (LUMIO) is a mission designed to observe, quantify, and

characterize the impacts of meteoroids on the Lunar far side and, therefore, complement in both space and time the observations currently taken from Earth. While Earth-based Lunar observations are restricted by weather, geometric and illumination conditions, a Moon-based observation campaign can improve the detection rate of impact flashes and the general quality and reliability of the final scientific product.

The mission has successfully completed the Phase A design, after successfully passing Phase 0 and an independent study in the ESA Concurrent Design Facility that has fully confirmed its feasibility. The LUMIO spacecraft is a 12U CubeSat with a mass of around 24 kg, released into Lunar orbit by a carrier spacecraft and capable of autonomously transferring from this initial parking orbit to its final destination, a halo orbit about the Earth–Moon L2 point from which permanent full-disk observation of the Lunar far side can be performed. The mission objectives will be achieved thanks to the LUMIO-Cam, a custom-designed optical instrument capable of detecting light flashes in the visible spectrum, and an innovative on-board data processing system, capable of drastically reducing the amount of information that needs to be transmitted back to Earth. The camera is capable of generating 2.6 TB/day of data, out of which only approximately 1 MB/day will need to be transmitted to Earth, since impact identification will be performed autonomously onboard and only relevant information will be actually transmitted.

This paper will present the current status of the mission, summarising the main results of the Phase A design and the way forward to the following steps in mission implementation (Phases B-C). The paper will include a summary of the spacecraft system design and mission analysis, as well as a description of various possible scenarios for the carrier spacecraft and the initial parking orbit. Particular focus will be given to the mission operations aspects, from both the science and communications point of view. The solutions adopted for the innovative autonomous navigation experiment, based on Moon images taken as a by-product by the LUMIO-cam during operations, will be described in detail, as well as the operational concept of the scientific data processing algorithm.