

IAF SPACE EXPLORATION SYMPOSIUM (A3)  
Moon Exploration – Part 1 (2A)

Author: Dr. Francesco Topputo  
Politecnico di Milano, Italy, francesco.topputo@polimi.it

Mr. Gianmario Merisio  
Politecnico di Milano, Italy, gianmario.merisio@polimi.it

Mr. Carmine Giordano  
Politecnico di Milano, Italy, carmine.giordano@polimi.it

Mr. Vittorio Franzese  
Politecnico di Milano, Italy, vittorio.franzese@mail.polimi.it

Dr. Mauro Massari  
Politecnico di Milano, Italy, mauro.massari@polimi.it

Dr. Pierluigi Di Lizia  
Politecnico di Milano, Italy, pierluigi.dilizia@polimi.it

Mr. Demetrio Labate  
Leonardo Spa, Italy, demetrio.labate@leonardocompany.com

Mr. Giuseppe Pilato  
Manpower c/o Leonardo, Italy, giuseppe.pilato.ext@leonardocompany.com

Dr. Emanuele Costa  
Leonardo Spa, Italy, emanuele.costa01@leonardocompany.com

Dr. Angelo Cervone  
Delft University of Technology (TU Delft), The Netherlands, a.cervone@tudelft.nl

Dr. Stefano Speretta  
Delft University of Technology (TU Delft), The Netherlands, s.speretta@tudelft.nl

Dr. Alessandra Menicucci  
Delft University of Technology (TU Delft), The Netherlands, A.Menicucci@tudelft.nl

Mr. Eric Bertels  
ISIS - Innovative Solutions In Space B.V., The Netherlands, E.BERTELS@ISISPACE.NL

Mr. A Thorvaldsen  
Norway, thorvaldsen@stcorp.no

Mr. A Kukharenka  
Norway, kukharenka@stcorp.no

Mr. Johan Vennekens  
ESA - European Space Agency, The Netherlands, Johan.Vennekens@esa.int

Dr. Roger Walker  
European Space Agency (ESA), The Netherlands, Roger.Walker@esa.int

CURRENT STATUS OF LUMIO MISSION: CHARACTERIZING LUNAR METEOROID IMPACTS  
WITH A CUBESAT

**Abstract**

The Lunar Meteoroid Impact Observer (LUMIO) is a mission designed to observe, quantify, and

characterize the impacts of meteoroids on the Lunar far side and, therefore, complement in both space and time the observations currently taken from Earth. While Earth-based Lunar observations are restricted by weather, geometric and illumination conditions, a Moon-based observation campaign can improve the detection rate of impact flashes and the general quality and reliability of the final scientific product.

The mission has successfully completed the Phase A design, after successfully passing Phase 0 and an independent study in the ESA Concurrent Design Facility that has fully confirmed its feasibility. The LUMIO spacecraft is a 12U CubeSat with a mass of around 24 kg, released into Lunar orbit by a carrier spacecraft and capable of autonomously transferring from this initial parking orbit to its final destination, a halo orbit about the Earth–Moon L2 point from which permanent full-disk observation of the Lunar far side can be performed. The mission objectives will be achieved thanks to the LUMIO-Cam, a custom-designed optical instrument capable of detecting light flashes in the visible spectrum, and an innovative on-board data processing system, capable of drastically reducing the amount of information that needs to be transmitted back to Earth. The camera is capable of generating 2.6 TB/day of data, out of which only approximately 1 MB/day will need to be transmitted to Earth, since impact identification will be performed autonomously onboard and only relevant information will be actually transmitted.

This paper will present the current status of the mission, summarising the main results of the Phase A design and the way forward to the following steps in mission implementation (Phases B-C). The paper will include a summary of the spacecraft system design and mission analysis, as well as a description of various possible scenarios for the carrier spacecraft and the initial parking orbit. Particular focus will be given to the mission operations aspects, from both the science and communications point of view. The solutions adopted for the innovative autonomous navigation experiment, based on Moon images taken as a by-product by the LUMIO-cam during operations, will be described in detail, as well as the operational concept of the scientific data processing algorithm.