

IAF ASTRODYNAMICS SYMPOSIUM (C1)
Guidance, Navigation and Control (1) (1)

Author: Mr. Atsushi Hori
NEC Corporation, Japan

Dr. Toshio Kamiya
NEC Corporation, Japan

DRAG-FREE CONTROL OF TIME-DELAY SYSTEM FOR FORMATION FLIGHT OF B-DECIGO
SPACECRAFT**Abstract**

B-DECIGO is a space gravitational wave telescope aimed at realizing the stage before DECIGO (Deci-hertz Interferometer Gravitational wave Observatory). Although the baseline length of B-DECIGO is 100km, which is one-tenth of the size of DECIGO, we aim to achieve observations as early as possible that cannot be made with terrestrial gravitational wave telescopes. B-DECIGO can observe gravitational waves generated from black-hole and neutron-star binary coalescences over almost the entire space. Besides, new observations not possible with the terrestrial gravitational wave telescope can be performed, such as by observing several months before the binary merger and predicting the merged time and position in advance. It also aims to unravel the mystery of galaxy formation by observing coalescences of black-hole binaries with an intermediate mass of about 1000 times the solar mass.

The formation control of a long-distance, drag-free, low-thrust, near-geostationary orbit satellite is presented, in view of future space gravitational wave observatory employing long baseline interferometry (100 km). For the purpose, a formation consisting of three drag-free satellites, orbiting at a fixed distance in a near-geostationary orbit, has been proposed. Formation fluctuations are bounded by a 40 m wide (along-track, cross-track and radial) box. This paper outlines position and attitude control problems of a long-distance three-satellite drag-free formation with time-delay system for the gravitational wave monitoring. The upper bound of the controller bandwidth is restricted by the system's time-delay, a precise control can be performed by multivariable controller with micro-newton thrusters. Simulated runs through spacecraft simulation, which is dominated by a drag, show that the first-trial design meets the tight control requirements, and demonstrates mission feasibility.