

29th IAA SYMPOSIUM ON SMALL SATELLITE MISSIONS (B4)
Constellations and Distributed Systems (7)

Author: Prof. Michele Grassi
University of Naples "Federico II", Italy

Prof. Antonio Moccia
University of Naples "Federico II", Italy

Prof. Roberto Opromolla
University of Naples "Federico II", Italy

Prof. Alfredo Renga
University of Naples "Federico II", Italy

Prof. Marco D'Errico
Seconda Università di Napoli, Italy

Dr. Alessio De Simone
University of Naples "Federico II", Italy

Prof. Gerardo Di Martino
Università degli Studi di Napoli "Federico II", Italy

Prof. Antonio Iodice
University of Naples "Federico II", Italy

Prof. Daniele Riccio
University of Naples "Federico II", Italy

Prof. Giuseppe Ruello
University of Naples "Federico II", Italy

Mr. Stefano Mungiguerra
Università degli Studi di Napoli "Federico II", Italy

Prof. Raffaele Savino
University of Naples "Federico II", Italy

Prof. Salvatore Amoruso
University of Naples "Federico II", Italy

Dr. Guido Di Donfrancesco
Italy

Dr. Valerio Pisacane
Eurosoft srl, Italy

Mr. Michele Cioffi
ALI S.c.a.r.l., Italy

Mr. Marco Fabio Miceli
ALI S.c.a.r.l., Italy

Dr. Francesco Punzo
ALI S.c.a.r.l., Italy

Dr. Giovanni D'Aniello
SRS E.D., Italy

Dr. Pietro Pasolini
SRS E.D., Italy

Abstract

The formation-flying synthetic aperture radar (FF-SAR) concept has been introduced in the last decades to enable new operational modes exploiting a set of compact and low-weight satellite platforms carrying receiving-only SAR antennas that simultaneously collect the signal emitted by a single spaceborne transmitter and scattered by the observed scene. FORCE is an industrial research project funded by the Italian Ministry for Scientific Research led by the University of Naples. It is conceived as a FF-SAR based on a close formation of N receivers, so that the coherent combination of the collected echoes can provide a Signal-to-Noise Ratio (SNR) up to N times the SNR of each individual receiver. Moreover, when more receivers are available, it is also possible to implement High-Resolution Wide-Swath (HRWS) techniques. FORCE is composed by a fleet of very compact bistatic receiving-only platforms that follows the transmitter at large distance (70-100 km), flying in a close formation (within 1 km) on a 410-km sun-synchronous orbit (97 inclination). Each platform is conceived with a modular architecture, i.e. as an assembly of CubeSat modules (up to 12). Hence, each subsystem is composed by one or more CubeSat modules and then these modules are assembled in a plug and play configuration to compose the overall platform. In this paper, both system and platform design will be described. Concerning system design, preliminary results on formation design and distributed payload performance will be reported focusing on two operating modes, namely SNR improvement and HRWS. The solution implemented for formation design exploits as much as possible the natural relative motion of the platforms in order to minimize the required V , that is provided by means of 2U hybrid micro-propulsion system. For 1-year demonstration mission the total required V is less than 7 m/s, with a 6-day maneuver frequency and a minimum V of about 6 cm/s. Concerning platform design, preliminary results on the development of the modules containing the deployable SAR antenna, the relative positioning and propulsion systems will be shown. The antenna is a 1-m mesh parabolic reflector that is deployed in orbit. In the folded configuration, antenna and deployment system are accommodated into a 3U module. The deployment is activated by a gas cartridge system which extracts the antenna hub. An additional pneumatic system is then activated to move away the feed from the antenna plane.