

20th IAA SYMPOSIUM ON VISIONS AND STRATEGIES FOR THE FUTURE (D4)
Innovative Concepts and Technologies (1)

Author: Prof. M.V. Sazhin

Sternberg Astronomical Institute of Moscow Lomonosov State University, Russian Federation

Dr. Margarita Safonova

The Indian Institute of Astrophysics, Bangalore, India

Prof. V. N. Sementsov

Sternberg Astronomical Institute of Moscow Lomonosov State University, Russian Federation

Dr. Priya Hasan

Maulana Azad National Urdu University, India

Prof. Najam Hasan

Maulana Azad National Urdu University, India

USING AN ARTSIMOVICH RAILGUN (RELSOTRON) FOR PAYLOAD DELIVERY FROM THE
MOON

Abstract

Long-term plans of exploration and utilization of the Moon, Mars, and outer space demand resolution of a large set of problems. One of the major problems concerns the return of the piloted lunar missions and the delivery of lunar minerals and material to Earth. In the present scenario, it is a high time to initiate the program of scientific exploratory research in the areas of creation and development of new (advanced) technologies, designed to support the space missions aimed at study, exploration and, ultimately, utilization of the lunar resources. One of the key problems in the large-scale exploration of the Moon is the high cost involved in delivering the spacecraft to the lunar surface and its return with lunar material to the Earth. We discuss here the unconventional methods of delivering payloads from the Moon to the Earth, namely, the concepts of the space elevator and the electromagnetic accelerator – the Artsimovich railgun (relsotron). By estimating the energy required to launch a payload into a low lunar orbit (LLO), or to the Lagrange point L1 of the Earth-Moon system, we show that the use of the relsotron to launch payloads from the lunar surface to these locations requires much less energy than the corresponding launches to the low-Earth orbit. The lunar relsotron can be built on the Moon using the local material and some necessary equipment from the Earth that needs to be delivered only once. The energy can be sourced using solar batteries on the lunar surface, or even a nuclear power sources delivered from the Earth. In the foreseeable future, a thermonuclear power source can be used, for which the fuel – ^3He isotope – is abundantly available on the Moon. Unlike on Earth where, in order to reduce the aerothermal heat load on the launched payload, the relsotron was suggested to be built high in the mountains with lengths of at least 1.5 km for a linear design, or with diameter of a few km for a circular design, the length of the linear lunar relsotron to launch to L1 can be just 157 mtrs. Therefore, we are confident that the use of the linear Artsimovich relsotron is a promising and cost-effective way of launching payloads from the surface of the Moon into the cislunar space; much more practical and economically feasible than the space elevator, or a conventional chemical rocket technology.