

IAF SPACE COMMUNICATIONS AND NAVIGATION SYMPOSIUM (B2)
Advances in Space-based Communication Systems and Services, Part 3 (4)

Author: Mr. Robin Bonny

Ecole Polytechnique Fédérale de Lausanne (EPFL), Switzerland, robin.bonny@alumni.epfl.ch

Mr. Martin Simik

Ecole Polytechnique Fédérale de Lausanne (EPFL), Switzerland, martin.simik@alumni.epfl.ch

Mr. Jérémy Weill

Ecole Polytechnique Fédérale de Lausanne (EPFL), Switzerland, jeremy.weill@epfl.ch

Ms. Juliette Challot

Ecole Polytechnique Fédérale de Lausanne (EPFL), Switzerland, juliette.challot@alumni.epfl.ch

Mr. Hannes Bartle

ClearSpace SA, Switzerland, hannes@clearspace.today

DEVELOPMENT OF A MODULAR HALF-DUPLEX FREQUENCY-AGILE X-BAND TRANSCEIVER
FOR CUBESATS AND ROBOTIC SPACECRAFT**Abstract**

The EPFL Spacecraft Team is developing the CHESS (Constellation of High-Energy Swiss Satellites) mission, foreseen to launch in 2025, a constellation consisting of two 3U CubeSats to study the chemical composition of Earth's exosphere, using time-of-flight mass spectrometry. In addition to a bidirectional UHF link, the satellites shall downlink the collected science data using a dedicated X-band transceiver. Given that the CubeSats are targeted for purely scientific and educational goals, the amateur frequency range from 10.45 to 10.50 GHz has been selected for operation. This amateur band provides sufficient bandwidth while considerably simplifying the frequency coordination process. As there is currently no off-the-shelf equipment available for this band, and the overall platform development for the CHESS mission is being conducted in-house, a custom solution for the transceiver is being developed.

The transceiver architecture presented in this contribution leverages SDR technology for easy adaptation to different applications. The selected SDR transceiver IC is coupled with a custom RF front-end to attain the target frequency beyond 10 GHz via a heterodyne approach, employing additional filtering. Modulation/demodulation and coding/decoding are performed on an adjacent Xilinx SoC. Given the modularity of this architecture, the desired frequency range can be changed by substituting a small number of components on the RF front-end, with the backbone remaining unchanged and without requiring a complete redesign of the system.

This modular technique can potentially be a good fit for future robotic spacecraft missions. Active Debris Removal (ADR) or Lifetime Extension (LE) services, for example, being developed by the EPFL Spin-off ClearSpace, require flexible communication systems that allow in-flight reconfigurability. There are currently no low-cost, frequency and transmit power agile Telemetry and Telecommand (TMTC) systems on the market. The Software Defined Radio (SDR)-based approach combined with modular front-end architectures at different frequency bands can provide a highly versatile solution for these types of missions.