

IAF MICROGRAVITY SCIENCES AND PROCESSES SYMPOSIUM (A2)
Fluid and Materials Sciences (2)

Author: Ms. Johanna Noria Brecher
Experimental Raumfahrt-Interessen Gemeinschaft e.V., Germany

Mr. Peter Ohr
Experimental Raumfahrt-Interessen Gemeinschaft e.V., Germany

Ms. Anja Müller-Brandes
Experimental Raumfahrt-Interessen Gemeinschaft e.V., Germany

Mr. Lars Klingenstein
Experimental Raumfahrt-Interessen Gemeinschaft e.V., Germany

Mr. Lennart Fox
Experimental Raumfahrt-Interessen Gemeinschaft e.V., Germany

Mr. Heiko Wickboldt
Experimental Raumfahrt-Interessen Gemeinschaft e.V., Germany

Mr. Jonas Sommerfeldt
Experimental Raumfahrt-Interessen Gemeinschaft e.V., Germany

Mr. Patrick Plörer
Experimental Raumfahrt-Interessen Gemeinschaft e.V., Germany

Mr. Arvid Lunding
Experimental Raumfahrt-Interessen Gemeinschaft e.V., Germany

Mr. Alexander Köhne
Experimental Raumfahrt-Interessen Gemeinschaft e.V., Germany

Dr. Aditya Thakur
Technische Universität Braunschweig, Germany

INVESTIGATION OF THE GRAVITATIONAL INFLUENCE ON THE IMPREGNABILITY OF
FIBER-THERMOPLASTICS**Abstract**

An ongoing area of research is the in-situ production of fiber composites through extrusion-based additive manufacturing, which facilitates sustainable and rapid production of customizable, net-shaped sub-assemblies. Incorporation of continuous fibers in composites enables the production of materials with improved properties, such as increased specific tensile strength and added multifunctionality. Although process and material efficient, this coextrusion approach is highly susceptible to void formation at the fiber-matrix interface. This is disadvantageous as it compromises the enriched material properties through fiber reinforcement. Molten thermoplastic exhibits the behavior of a non-Newtonian fluid, changing wettability under varying gravitational conditions. Therefore, manufacturing under microgravity could result in a different void fraction. To achieve prolonged microgravity conditions, a REXUS sounding rocket is utilized. The objective of the Carbon REinforced Additive manufacturing Technology Experiment (CREATE) is to improve the understanding of the influence of gravity on fiber-matrix impregnation in additive manufacturing of fiber composites. In the evaluation, the samples are examined microscopically and material properties such as tensile strength and electric conductivity are measured. A comparison with samples produced on Earth will show the gravitational influence on the interfacial behavior. The

investigated material combination is a polylactic acid (PLA) matrix reinforced with endless carbon fibers. These were selected due to availability, modularity, and comparability reasons. Furthermore, PLA has a lower melting point than PETG or PEEK, thus less energy is required to melt the filament. CREATE will perform fundamental research in the field of fiber-reinforced additive manufacturing, while simultaneously improving composite manufacturing technologies for terrestrial applications.