

IAF SPACE COMMUNICATIONS AND NAVIGATION SYMPOSIUM (B2)
Advances in Space-based Communication Technologies, Part 1 (5)

Author: Dr. Peter Joonghyun Ryu
SPACEMAP Inc., Korea, Republic of, peter.ryu@spacemap42.com

Dr. Jaedong Seong
Korea Aerospace Research Institute (KARI), Korea, Republic of, acestars@kari.re.kr

Mr. Shawn Seunghwan Choi
SPACEMAP Inc., Korea, Republic of, shawn.choi@spacemap42.com

Mr. Chanyoung Song
Hanyang University, Korea, Republic of, cysong.vdrc@gmail.com

Mr. Hyunwoo Kim
Korea, Republic of, hwkim.vdrc@gmail.com

Mr. Junhee Jang
Korea, Republic of, jhjang.vdrc@gmail.com

Mr. Minwoo Ji
Korea, Republic of, mwji.vdrc@gmail.com

Mr. Jongwon Kim
SPACEMAP Inc., Korea, Republic of, john.kim@spacemap42.com

Ms. Seongae Kim
SPACEMAP Inc., Korea, Republic of, so.kim@spacemap42.com

Prof. Douglas Deok-Soo Kim
SPACEMAP Inc., Korea, Republic of, douglas.kim@spacemap42.com

RADIO FREQUENCY INTERFERENCE: ITS PREDICTION AND AVOIDANCE BY
WATCHERCATCHER IN SPACEMAP

Abstract

As more satellites are being deployed, spectrum space is becoming more congested by their radio frequency (RF) for communications to/from both ground stations and other satellites. One of the critical consequences of the congested spectrum space and busy geo-space is radio frequency interference (RFI) which may cause serious communication disruption. This phenomenon will be outstanding as more constellations will be in orbits. Therefore, the prediction of RFI, and hopefully followed by its mitigation, is crucial for smooth communication. However, the prediction and mitigation are computational challenges for the satellites orbiting at extreme speeds, particularly in the forthcoming constellations of from hundreds to thousands, if not tens of thousands, of satellites. This is because an RFI occurs under specific geometric conditions involving three or sometimes four objects at least, depending on conditions. So, the size of the combinatorial space is of $(N, 3)$ or $(N, 4)$ for each moment in timeline. The cases of higher combinatorial space may not be ignorable. Here we introduce the SPACEMAP feature which can efficiently and accurately predict the RFI of own satellites against all known radio-frequency emitting objects in space catalogue. We take advantage of the already-available WatcherCatcher function where the anchor point can be a location not only in a 2D plane but also in a 4D spatiotemporal space, i.e., flying airplane and satellites. The efficiency of SPACEMAP is possible by taking an advantage of Voronoi diagrams' powerful spatial reasoning features. Assuming a preprocessing operation to construct the Voronoi diagram over timeline, the SPACEMAP method can solve many challenging spatiotemporal problems very fast, i.e.,

near real-time if not truly real-time. This study makes the following additional contributions. First, the method used for the RFI prediction can be similarly used to find a way for RFI deconfliction. Second, the RFI prediction provides a mitigate scheme to avoid corrupted communication due to noise. SPACEMAP runs on AWS and exploits elastic compute and auto scaling features. SPACEMAP currently uses the TLE data from Space-Track and its services are available at <https://platform.spacemap42.com>.