IAF MATERIALS AND STRUCTURES SYMPOSIUM (C2) Advancements in Materials Applications and Rapid Prototyping (5)

Author: Ms. Tiziana Biasutti Politecnico di Milano, Italy

Mr. Paolo Bettini Politecnico di Milano, Italy Dr. Adelaide Nespoli Consiglio Nazionale delle Ricerche (CNR), Italy Dr. Antonio Grande Politecnico di Milano, Italy Dr. Tanya Scalia Italian Space Agency (ASI), Italy Dr. Marta Albano Agenzia Spaziale Italiana (ASI), Italy Prof. Bianca Maria Colosimo Politecnico di Milano, Italy Prof. Giuseppe Sala Politecnico di Milano, Italy

3D PRINTING OF SHAPE MEMORY ALLOYS FOR COMPLEX ARCHITECTURES OF SMART STRUCTURES

Abstract

Shape Memory Allovs are materials used to design smart structures with intrinsic functional properties and improved efficiency. This is a key aspect of aerospace industry and make SMA good candidates in this field. One of the most diffused SMA is NiTiNOL which, however, has the strong limitation of poor machinability, so only simple shapes can be obtained. Additive Manufacturing processes allow to overcome this limit and to design complex shapes. Compared to other metallic materials, the optimization of the process is complicated because, beside mechanical properties and presence of defects, considerable attention needs to be dedicated to the material functionality. The high temperatures of the process significantly affect the material properties, leading to possible evaporation of Ni and formation of precipitates. The paper is focused on the optimization of process parameters to ensure optimal pseudo-elastic behaviour, which is essential for the design of structural dampers. This was accomplished starting from simple structures and then designing a damper that couples the pseudoelasticity of NiTi with load support capacity. A pseudoelastic powder (50.8% at. of Ni) was initially characterized. This was performed through the observation of SEM images, DSC, XRD, and EBS. After that, some cubic samples were manufactured, with the dimension of $3 \ge 3 \ge 5$ mm³ and $3 \ge 3 \ge 18$ mm³. A set of different power densities and scan speeds were used to find the best set of process parameters. The specimens were firstly evaluated based on their density. Specimens with density higher than 99.5% were the ones with the best performances. On each sample were performed DSC analyses on as-built and treated specimens and mechanical tests. Moreover, tomography followed by microscope observations investigate the presence of defects associated with different manufacturing parameters.

The samples were tested in compression, with static cyclic loading at different strains, increasing it up to 8%. The residual strain for cyclic loading at 4% is less than 1%, so good recovery of the deformation was

shown. Moreover, numerical analyses that model the pseudoelastic behaviour in compression tests were implemented.

Finally, due to the good pseudoelastic performance obtained on simple specimens, an innovative concept of structural dampers with functional properties and complex shapes was preliminary designed.