

IAF SPACE POWER SYMPOSIUM (C3)  
Interactive Presentations - IAF SPACE POWER SYMPOSIUM (IP)

Author: Dr. Dominika Capkova  
Pavol Jozef Safarik University, Slovak Republic, dominika.capkova@upjs.sk

Dr. Miroslav Almáši  
Pavol Jozef Safarik University, Slovak Republic, miroslav.almasi@upjs.sk

Dr. Andrea Straková Fedorková  
Pavol Jozef Safarik University, Slovak Republic, andrea.fedorkova@upjs.sk

Dr. Tomáš Kazda  
Brno University of Technology, Czech Republic, kazda@feec.vutbr.cz

## DEVELOPMENT OF HIGH-POWER LITHIUM-SULFUR BATTERIES FOR SPACE MISSIONS

### Abstract

The essential requirement for the satellite components is high dependability due to expensive replacement of new satellite. Space missions during the eclipse are powered by batteries which directly determine the service life and functions of spacecraft. The batteries should possess high power, energy density, Coulombic efficiency, light-weight, and wide temperature operation range. The preferred energy source in space missions are lithium-ion (Li-ion) batteries due to their high power, energy density, and Coulombic efficiency [1,2]. Li-ion batteries have already completed many space flights, proving that the technology is mature. However, many space missions require batteries with even higher energy density that is provided by Li-ion batteries. Lithium-sulfur (Li-S) batteries are probably going to be the next-generation of energy storage to replace them.

The main advantage of Li-S technology is its theoretical energy density which is approximately five times higher than that of Li-ion cells. Moreover, sulfur is an abundant element and environmentally friendly. The major obstacle to the successful application of Li-S battery cells is dissolution of polysulfide intermediates and their shuttling between electrodes. The consequence of this phenomenon is loss of active material, fast capacity decay, low efficiency, and high self-discharge rate. Sulfur during charging changes its density resulting in volumetric expansion up to 80 % which may negatively affect the cathode material. Highly porous supporting materials for sulfur may suppress the influence of negative issues. Metal-organic framework (MOF) materials represent a novel class of materials with unique porous structure for sulfur confinement [3].

Herein, MOF-74 was proposed as a support for sulfur in cathode material for Li-S batteries. MOF-74 is a honeycomb-like material formed by the combination of divalent metal ions and 2,5-dihydroxyterephthalic acid. The sulfur-based electrode material containing MOF-74 showed low capacity decay despite 100 cycles at 0.5 C.

### Acknowledgment

This research was sponsored by specific graduate research of the Brno University of Technology No. FEKT-S-20-6206, by the Slovak Research and Development Agency under contracts No. APVV-20-0512, APVV-20-0138, and ITMS2014+: 313012BUN5, which is part of the Important Project of Common European Interest (IPCEI), called European Battery Innovation in the Operational Program Integrated Infrastructure, call code: OPII-MH/DP/2021/9.5-34, co-financed from the resources of the European Re-

gional Development Fund.

#### References

- [1] E. Sanchis et al., IEEE Transactions on Industrial Electronics, 57 (2010) 3935-3943.
- [2] Y. Song et al., IEEE Transactions on Industrial Electronics, 68 (2021) 12375-12384.
- [3] Z. Cong et al., Journal of Alloys and Compounds, 924 (2022) 166486.