

IAF SPACE PROPULSION SYMPOSIUM (C4)  
Interactive Presentations - IAF SPACE PROPULSION SYMPOSIUM (IP)

Author: Mr. Claudio Antonio Morales Benítez  
High Technology Unit (UAT) Faculty of Engineering - UNAM, Mexico

Mr. Ángel Perez  
Universidad Nacional Autónoma de México (UNAM), Mexico  
Ms. Arantxa Mendoza Collado  
High Technology Unit (UAT) Faculty of Engineering - UNAM, Mexico  
Mr. Diego Fernando Maya Hernández  
High Technology Unit (UAT) Faculty of Engineering - UNAM, Mexico  
Mr. Elias Basaldua  
High Technology Unit (UAT) Faculty of Engineering - UNAM, Mexico  
Mr. Fabián Sánchez Hernández  
High Technology Unit (UAT) Faculty of Engineering - UNAM, Mexico  
Ms. Natalie Jimena Roldán Cruz  
High Technology Unit (UAT) Faculty of Engineering - UNAM, Mexico  
Ms. Ximena Zepeda Sandoval  
Universidad Nacional Autónoma de México (UNAM), Mexico

IMPROVING ROCKET NOZZLE EFFICIENCY WITH ROUGH SURFACES

**Abstract**

Turbulence is one of the most chaotic and unpredictable phenomena in physics and it affects the aerodynamic performance of flying bodies. Therefore, being able to prevent and control the turbulent effects during the process of design is convenient. Doing so not only reduces the risk margin, but also improves flight performance, which has positive impacts on aspects such as stability and fuel efficiency that in turn provokes decreases in cost and also promotes care for the environment, which is a very important factor in the actual world. There have been studies of the behavior of shark skin in the water and it has been observed that the riblets on it help to reduce drag by controlling turbulence in the boundary layer, which allows sharks to swim faster and with less energy expenditure. Since water is a fluid, similar to air, we can expect it to behave similarly. The present research focuses on applying different types of roughness to the inner surface of the divergent section of a rocket nozzle in order to determine the changes in the working fluid properties and analyze the resulting increase of the aerodynamic performance through computational simulations and comparisons with a smooth surface.