

30th IAA SYMPOSIUM ON SMALL SATELLITE MISSIONS (B4)  
Interactive Presentations - 30th IAA SYMPOSIUM ON SMALL SATELLITE MISSIONS (IP)

Author: Prof.Dr. Cristian Vendittozzi  
Universidade de Brasília, Brazil, vendittozzi@unb.br

Dr. Ignazio Dimino  
CIRA Italian Aerospace Research Center, Capua, Italy, i.dimino@cira.it

Prof.Dr. William Silva  
University of Brasilia, Brazil, reis.william@unb.br

Prof. Rafael Mendes  
University of Brasilia, Brazil, rafael.mendes@unb.br

Prof. Francesco Marra  
University of Rome “La Sapienza”, Italy, francesco.marra@uniroma1.it

Dr. Laura Paglia  
Sapienza University of Rome, Italy, laura.paglia@uniroma1.it

MULTIDISCIPLINARY DESIGN GUIDELINES FOR A 12U CUBESAT  
DEPLOYABLE AEROSHELL FOR ATMOSPHERIC REENTRY MISSIONS

**Abstract**

In recent years, the use of the CubeSat class of satellites has increased exponentially and, while initially intended for the development of university projects, often limited in ambition, it is now proving to be highly versatile and suitable for more complex applications. Ensuring a deorbiting capability to reduce the risks associated with the generation of new space debris and the ability to perform controlled reentry to enable new scientific and commercial missions in low Earth orbit is now becoming critical. This paper presents guidelines for the design of the reentry mission of a CubeSat capable of returning a payload to the ground that could consist of experiments conducted on LEOs, to name one conceivable scenario, focusing on spacecraft geometry, mission design (orbits and maneuvers), and preliminary analysis of the main aerothermodynamic coefficients. The project focuses mainly on the flexible heat shield design of the SPLASH (Self-deployable Flexible AeroShell for de-Orbiting and Space Re-entry), a project established as a joint technology development program, co-financed by Brazil and Italy. The aeroshell is meant to protect the bus and the mission payload, it must be stowed in the smallest possible volume of the CubeSat, seeking an optimized folding configuration, and must be able to unfold, deployed when required and controlled by Shape Memory Alloy (SMA) actuators - facilitating deorbiting - stabilize during a controlled re-entry and finally be recovered.