

IAF SPACE COMMUNICATIONS AND NAVIGATION SYMPOSIUM (B2)
Advances in Space-based Navigation Systems, Services, and Applications (7)

Author: Mr. Stefano Casini
TU Delft, The Netherlands, s.casini@tudelft.nl

Dr. Angelo Cervone
Delft University of Technology (TU Delft), The Netherlands, a.cervone@tudelft.nl

Dr. Bert Monna
AAC Hyperion, The Netherlands, bert.monna@aac-clydespace.com

Dr. Pieter Visser
Delft University of Technology (TUD), The Netherlands, P.N.A.M.Visser@tudelft.nl

SIMULATION OF DEEP-SPACE AUTONOMOUS LINE-OF-SIGHT NAVIGATION USING
SYNTHETIC IMAGES IN THE LOOP**Abstract**

Autonomous Line-of-Sight navigation represents an appealing technique that can be exploited by deep-space spacecraft, particularly miniaturized, to estimate the state during cruising. It is based on the observation of visible bodies' directions, processed onboard to estimate the spacecraft' 6D heliocentric state. Its applicability has been preliminarily investigated by feeding the navigation filter with simplified measurements, simulated by adding a certain noise on the actual direction, based on star-tracker characteristics. However, while this approach is convenient and appropriate for a preliminary study, it is not sufficient to dive into the characteristics and performance of the method, and later on to definitely prove its applicability to real missions. This is because the measurement error cannot be considered relying exclusively on the star trackers characteristics, as the observation scenario (e.g. planet apparent size, illumination condition, stars background) does play an important role in the measurement error.

For this reason, in this work, we include image processing in the simulation loop. First, we define how to simulate realistic and reliable synthetic space images as a function of hardware characteristics and observation scenarios; then we use the generated images within the simulation to compute the measurements. Thanks to this approach, it is also possible to further improve the navigation filter design. In fact, we developed an Adaptive Extended Kalman Filter (AEKF) to cope with variable measurement errors and dynamics conditions. This filter allows the automatic tuning of both the process noise covariance and the measurement noise matrices as a function of the scenario.

With this approach, we explore also the differences between an active navigation strategy, based on re-orientating the spacecraft to focus sequentially on the planet in the Field-of-View (FoV), and a passive navigation strategy, which exploits a scenario-based optimized cameras orientation to maximize the observation time length of visible bodies without performing manoeuvres.

Finally, we compare the analysis with and without the space image simulator in the loop, showing how without implementing the latter, the actual performance cannot be completely investigated. In fact, the positioning error mean values are comparable, but they have mismatches during the simulation length.

With this work, we add three important pieces to the road map for fully autonomous deep-space spacecraft: performance evaluation refinement including image-processing, design of AEKF for the technique, and evaluation of passive navigation strategy. This work has been developed within the European Union ITN Stardust-R framework.