

IAF SPACE EXPLORATION SYMPOSIUM (A3)  
Moon Exploration – Part 2 (2B)

Author: Dr. Michael Holik  
Institute of Experimental and Applied Physics, Czech Technical University in Prague, Czech Republic,  
michael.holik@cvut.cz

Dr. Robert Filgas  
Czech Technical University In Prague (CTU), Czech Republic, robert.filgas@utef.cvut.cz

Mr. Milan Malich  
Czech Technical University In Prague (CTU), Czech Republic, milan.malich@cvut.cz

Mr. Farid Ahmadov  
Azerbaijan National Academy of Sciences, Azerbaijan, farid-akhmedov@yandex.ru

Dr. Gadir Ahmadov  
Azerbaijan, ahmadovgadir@gmail.com

Mr. Ondrej Urban  
University of West Bohemia, Czech Republic, urbano@fel.zcu.cz

Mr. Ondrej Pavlas  
Institute of Experimental and Applied Physics, Czech Technical University in Prague, Czech Republic,  
ondrej.pavlas@cvut.cz

Dr. Azer Sadigov  
Azerbaijan, saazik626@gmail.com

THE HARDGAMM SPECTROMETER PAYLOAD FOR EXTRA-TERRESTRIAL SEARCHING FOR  
HYDROGEN PRESENCE AND OTHER CONSTITUENTS OF INTEREST APPLYING  
NON-INVASIVE METHOD OF CHARACTERISTIC GAMMA PHOTON DETECTION**Abstract**

Neutron and  $\gamma$ -ray spectrometers are used in state-of-the-art planetary research for studying the elemental composition of planets and small bodies of the solar system. Instead of looking for water itself, a suite of instruments will look for gamma rays emitted by hydrogen. Knowing well the energies of characteristic gamma photons allows us to recognize the presence of hydrogen or other constituents of interest. Hence, having a gamma spectrometer payload is important to analyze gamma rays and evaluate the concentrations of hydrogen from the intensities of  $\gamma$ -ray lines to find hydrogen-containing substances, primary water and water ice. The miniaturized electronics occupying a minor portion of a payload while maximizing an active volume filled with a sensitive element allows to achieve high efficiency for the detection of gamma-rays. The presented concept of HardGamm payload integrates a novel MAPD-3NM sensor array (of silicon photomultiplier type) based detector assembled with LaBr<sub>3</sub>(Ce), BGO and NaI scintillation materials (high-Z and light yield) the combination which already proved to be a very effective and compact size laboratory instrument in gamma spectroscopy. The total number of pixels (974 728 pixels) and high photon detection efficiency (>30%) of the novel MAPD-3NM sensor array allowed getting good energy resolution in energy range of MeVs. The adaptation into the form of HardGamm payload deals with common disadvantages of silicon photomultiplier like detectors to compensate and overcome them in order to design the spectrometer payload capable of operation in harsh conditions of extra-terrestrial mission while keeping sufficient detection performance and energetic resolution for recognition of characteristic gammas, thus to confirm presence of material constituents.